

FRANK'S TONG SELECTION CHART

	High Gear RPM/Torque	Low Gear RPM/Torque	Handle Length	Weight	Size Range	Additional Features
Dual String Tong	30 rpm @ 4,000 ft-lb	13 rpm @ 7,500 ft-lb	24"	900 lb (408 kg)	1" - 3 1/2"	2,3
4 1/2" T-2000 Tong	33 rpm @ 4,000 ft-lb	7.5 rpm @ 15,000 ft-lb	24"	1,100 lb (499 kg)	1" - 4 3/4"	1,2,3
4 1/2" T-2001 Tong	50 rpm @ 2,700 ft-lb	11.5 rpm @ 12,000 ft-lb	24"	1,150 lb (521 kg)	1" - 4 3/4"	1,2,3
7 5/8" Tong	114 rpm @ 4,000 ft-lb	7.5 rpm @ 25,000 ft-lb	39"	1,275 lb (578 kg)	4 1/2" - 7 5/8"	2,3
7 5/8" High Torque Tong	60 rpm @ 5,600 ft-lb	11.3 rpm @ 30,000 ft-lb	39"	1,300 lb (590 kg)	4 1/2" - 7 5/8"	2,3
10 3/4" Tong	91 rpm @ 5,140 ft-lb	15 rpm @ 28,000 ft-lb	39"	1,450 lb (658 kg)	5 1/2" - 10 3/4"	2,4
14" Tong	92 rpm @ 4,800 ft-lb	15.4 rpm @ 29,000 ft-lb	41"	1,800 lb (816 kg)	5 1/2" - 13 5/8"	2,4
14" High Torque Tong	65 rpm @ 8,000 ft-lb	9 rpm @ 44,000 ft-lb	41"	1,800 lb (816 kg)	5 1/2" - 13 5/8"	2,4
14 3/8" Tong	34.6 rpm @ 11,000 ft-lb	8.2 rpm @ 65,000 ft-lb	41"	3,350 lb (1,520 kg)	7" - 14 3/8"	1,2,4
14 3/8" Riser Tong	34.6 rpm @ 11,000 ft-lb	8.2 rpm @ 65,000 ft-lb	N/A	5,000 lb (2,270 kg)	7 5/8" - 14 3/8"	1,2,3
21" Tong	64 rpm @ 6,000 ft-lb	7.5 rpm @ 79,000 ft-lb	52"	4,700 lb (2,130 kg)	10 3/4" - 21"	1,2,4
21" Riser Tong	64 rpm @ 6,000 ft-lb	7.5 rpm @ 79,000 ft-lb	N/A	6,800 lb (3,090 kg)	10 3/4" - 21"	1,2,3
XT22	19.2 @ 7,000 ft-lb	2.1 rpm @ 100,000 ft-lb	50"	4,600 lb (2,090 kg)	14" - 22"	1,2,4
36" Tong	21.1 rpm @ 23,000 ft-lb	4.7 rpm @ 105,300	74"	7,400 lb (3,357 kg)	24" - 36"	1,2
	Additional Features:	1) Hydraulic Shift	2) Optimized Camming System	3) Standard Integral Back-Up	4) Optional Integral Back-Up	

For more information call 1-800-833-7265 or e-mail info@frankscasing.com
www.frankscasing.com

Copyright © 2003 Frank's Casing Crew & Rental Tools, Inc., Lafayette, LA